

NYLOY® KF-0010N 6151W

Polyamide
Nytex Composites Co., Ltd.

Message:
NYLOY® KF-0010N 6151W is a Polyamide material. It is available in Asia Pacific or North America. Primary attribute of NYLOY® KF-0010N 6151W: Flame Rated.

General Information			
Appearance	White		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.56	g/cm ³	ASTM D792
Molding Shrinkage			ASTM D955
Flow	0.72	%	
Across Flow	0.58	%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	56.9	MPa	ASTM D638
Tensile Elongation (Break)	0.80	%	ASTM D638
Flexural Modulus	12500	MPa	ASTM D790
Flexural Strength	98.0	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.18 mm)	27	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	195	°C	ASTM D648
Thermal Conductivity			ASTM E1461
-- ¹	2.0	W/m/K	
-- ²	6.0	W/m/K	
Electrical	Nominal Value	Unit	Test Method
Surface Resistivity	1.0E+14	ohms	ASTM D257
Flammability	Nominal Value	Unit	Test Method
Flame Rating (1.60 mm)	V-0		UL 94
Additional Information	Nominal Value	Unit	
Breakdown Voltage	> 5000	V	
NOTE			
1.	Through-plane		
2.	In-plane		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

