

Hifax TRC 495P G13076

Polypropylene Copolymer

LyondellBasell Industries

Message:

Hifax TRC 495P G13076 is a 16% talc filled PP copolymer, with superior impact/stiffness balance, excellent flowability, good processability and good UV resistance. The product is also available as a customized color matched, pellet form. This grade is delivered in G13076 color version.

This grade is not intended for medical, pharmaceutical, food and drinking water applications.

General Information			
Filler / Reinforcement	Talc filler, 16% filler by weight		
Features	Rigid, good		
	Copolymer		
	Impact resistance, good		
	Good UV resistance		
	Workability, good		
	Good liquidity		
Uses	Outdoor application		
Appearance	Available colors		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	1.00	g/cm ³	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	20	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus ¹ (23°C)	1700	MPa	ISO 178/A
NOTE			
1.	1.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT