

# VisiJet® FTX Gray

Unspecified

3D Systems

## Message:

VisiJet FTX Gray shows off every detail and is ready for painting  
UV Curable Plastic  
Primer gray general purpose

General Information			
Features	Pure/High Purity		
Uses	Mold Making		
	Forming		
	Forming material		
Appearance	Grey		
Forms	Liquid		
Processing Method	stereolithography		
Physical	Nominal Value	Unit	
Density <sup>1</sup>	1.12	g/cm <sup>3</sup>	
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	1290	MPa	ASTM D638
Tensile Strength	28.0	MPa	ASTM D638
Tensile Elongation (Break)	6.2	%	ASTM D638
Flexural Strength	38.0	MPa	ASTM D790
NOTE			
1.	Liquid @ 25°C		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT