

Sylvin 6427-62UV Natural

Thermoplastic Elastomer

Sylvin Technologies Incorporated

Message:

Sylvin 6427-62UV Natural Is An Elastomer Compound Formulated For Jacketing Applications That Require Superior Low Temperature Flexibility With Improved Flame Retardant Properties. This Compound Contains An Ultra Violet Stabilizer.

General Information			
Additive	UV stabilizer		
Features	Flexibility at low temperatures		
	Flame retardancy		
Uses	Cable sheath		
	Wire and cable applications		
Appearance	Natural color		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.22	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	62		ASTM D2240
Shaw A, 10 seconds	62		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	11.7	MPa	ASTM D638
Tensile Elongation (Break)	420	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	35.0	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	166 - 177	°C	
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	25	%	ASTM D2863

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

