

Sylvin 8684-75C Clear

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:
Sylvin 8684-75C Clear Is A Vinyl Compound Formulated With Improved Stability For Extrusion Applications.

General Information			
Additive	Unspecified Stabilizer		
Features	Good Stability		
Appearance	Clear/Transparent		
Processing Method	Extrusion		
Hardness	Nominal Value	Test Method	
Durometer Hardness (Shore C, 10 sec)	75	ASTM D2240	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	19.7	MPa	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	105	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	177 to 191	°C	
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	25	%	ASTM D2863

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT