

# DOW™ LLDPE 1630

Linear Low Density Polyethylene Resin

The Dow Chemical Company

## Message:

Dow LLDPE 1630 is a Linear Low Density Polyethylene Resin, 1-hexene copolymer, produced in the Solution Process. This resin is designed to be used in cast extrusion to produce films for industrial applications and consumer packaging.

Complies with:

U.S. FDA, 21 CFR 177.1520(c)3.2a

Europe EU Commission Regulation (EU) No 10/2011 (See NOTES)

Consult the regulations for complete details.

General Information			
Agency Ratings		EU No 10/2011	
		FDA 21 CFR 177.1520(c) 3.2a	
Forms		Pellets	
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.918	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	3.0	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

