Mowiol® 23-88

Polyvinyl Alcohol

Kuraray Co., Ltd.

Message:

Partially hydrolysed grade

Mowiol[®] and Kuraray Poval[®] are the trade name of the polyvinyl alcohols marketed by Kuraray. These are manufactured from polyvinyl acetate by alcoholysis using a continuous process. By varying the degree of polymerization of the polyvinyl acetate and its degree of hydrolysis (saponification), a number of different grades can be supplied. Our PVOH types are offered in a high standard purity showing especially "low ash and VOC contents".

| General Information | | | |
|-----------------------------------|---------------------------------|----------|-------------|
| Features | Barrier Resin | | |
| | Biodegradable | | |
| | Good Adhesion | | |
| | Good Colorability | | |
| | Water Soluble | | |
| | | | |
| Uses | Adhesives | | |
| | Binder | | |
| | Building Materials | | |
| | Coating Applications | | |
| | Film | | |
| | Foil Coatings | | |
| | Paper Coatings | | |
| | Textile Applications | | |
| | | | |
| Forms | Granules | | |
| Physical | Nominal Value | Unit | Test Method |
| Apparent Density | 0.40 to 0.60 | g/cm³ | DIN 53466 |
| Solution Viscosity ¹ | 22 to 25 | mPa∙s | DIN 53015 |
| Ash Content ² | < 0.50 | % | |
| Ester Content | 130 to 150 | mg KOH/g | DIN 53401 |
| pH ³ | 4.5 to 7.0 | | DIN 19261 |
| Degree of Hydrolysis ⁴ | 87 to 89 | % | |
| Methanol Extractables | < 3.0 | % | |
| Non-Volatile Content ⁵ | 95 | % | DIN 53189 |
| Residual Acetyl Content | 10 to 12 | % | |
| NOTE | | | |
| 1. | 4 % aqueous solution at 20 °C | | |
| 2. | Calculated as Na2O | | |
| 3. | 4 % solution in distilled water | | |
| 4. | Saponification | | |
| | | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

