Zhongfa PP pp1

Polypropylene

Yuyao Zhongfa Engineering Plastics Co. Ltd.

Message:

Zhongfa PP pp1 is a polypropylene material. This product is available in the Asia-Pacific region and is processed by injection molding. The main features of Zhongfa PP pp1 are: high gloss chemical resistance Heat resistance The typical application field of Zhongfa PP pp1 is: automotive industry

| General Information | | | |
|--|---------------------------------|----------|-------------|
| Features | Highlight | | |
| | Good liquidity | | |
| | Good chemical resistance | | |
| | Heat resistance, high | | |
| | | | |
| Uses | Application in Automobile Field | | |
| Forms | Particle | | |
| Processing Method | Injection molding | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 0.910 | g/cm³ | ASTM D792 |
| Melt Mass-Flow Rate (MFR) | 3.0 | g/10 min | ASTM D1238 |
| Molding Shrinkage - Flow | 1.8 | % | ASTM D955 |
| Hardness | Nominal Value | Unit | Test Method |
| Rockwell Hardness (R-Scale) | 98 | | ASTM D785 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength | 35.0 | MPa | ASTM D638 |
| Tensile Elongation (Break) | 100 | % | ASTM D638 |
| Flexural Modulus | 1400 | MPa | ASTM D790 |
| Flexural Strength | 38.0 | MPa | ASTM D790 |
| Thermal | Nominal Value | Unit | Test Method |
| Deflection Temperature Under Load (0.45 | 100 | | |
| MPa, Unannealed) | 120 | °C | ASTM D648 |
| Additional Information | | | |
| Aging Resistance at 150°C: >350 hrNotched Izod Impact, ASTM D256: 3.5 kJ/m ² Unnotched Izod Impact, ASTM D256: No Break | | | |
| | Nominal Value | Unit | |
| Drying Temperature | 90.0 - 95.0 | °C | |
| Drying Time | 2.0 - 3.0 | hr | |
| Processing (Melt) Temp | 195 - 225 | °C | |
| Mold Temperature | 45.0 - 80.0 | °C | |
| Injection Pressure | 60.0 - 90.0 | MPa | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

