

LTP CT-1215

Polyphenylene Sulfide
Chengdu Letian Plastics Co., Ltd

Message:

Resin of LTP CT-1200 serials is a kind of engineering plastic with high performance based on PPS. For its outstanding thermal transmittance and insulation ability, life-time service around 180-220°C, the materials are suitable for produce varied shell or capsulation for electric heating element and electric appliance element with high elimination of heat.

General Information			
Features	High Heat Resistance		
Uses	Electrical/Electronic Applications		
Appearance	Colors Available		
Physical	Nominal Value	Unit	Test Method
Density	1.75	g/cm ³	GB/T 1033
Molding Shrinkage ¹ (4.00 mm)	0.30 to 0.60	%	
Water Absorption (Saturation, 23°C)	0.20 to 0.40	%	GB/T 1034
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress	80.0	MPa	GB/T 1040
Tensile Strain (Break)	1.0	%	GB/T 1040
Flexural Modulus	10000	MPa	GB/T 1042
Flexural Stress	100	MPa	GB/T 1042
Thermal	Nominal Value	Unit	Test Method
Specific Heat	1000	J/kg/°C	ASTM E1461
Thermal Conductivity	15	W/m/K	ASTM E1461
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	1.0E+11	ohms·cm	GB/T 1410
NOTE			
1.	80x80x4 mm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT