

# NEXUS PP CPP25/NB

Polypropylene Impact Copolymer

Nexus Resin Group, LLC.

## Message:

Impact Copolymer for Injection Molded Applications

Nexus CPP25/NB is very high impact, no break copolymer used for injection applications requiring a higher melt flow, superior toughness and impact.

General Information			
Features	Good Toughness		
	High Flow		
	High Impact Resistance		
	Impact Copolymer		
Processing Method		Injection Molding	
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	25	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	229	MPa	ASTM D638
Flexural Modulus	1070	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	No Break		ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT