

Petrothene® XL07505

Ethylene Vinyl Acetate Copolymer
LyondellBasell Industries

Message:

Petrothene XL07505 is a colorable, non-halogenated, flame retardant compound crosslinkable via continuous vulcanization (C.V.).

General Information		
Additive	Flame retardancy	
Features	Crosslinkable	
	Halogen-free	
	Flame retardancy	
Uses	Wire and cable applications	
Processing Method	Wire & Cable Extrusion	
Physical	Nominal Value	Unit
Density (23°C)	1.40	g/cm³
Mechanical	Nominal Value	Unit
	19.3	
Tensile Strength ¹ (Break)	19.3	MPa
Tensile Elongation ² (Break)	220	%
Aging	Nominal Value	Unit
Retention of Tensile Stress at Break	100	%
Elongation retention rate	85	%
NOTE		
1.	Initial	
2.	Initial	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT