

WPP PP PPC3GF2.5-UV Black

Polypropylene Impact Copolymer

Washington Penn Plastic Co. Inc.

Message:

WPP PP PPC3GF2.5-UV Black is a Polypropylene Impact Copolymer (PP Impact Copolymer) product filled with 25% glass fiber. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America.

Characteristics include:

- Copolymer
- High Stiffness
- Impact Resistant
- UV Stabilized

General Information			
Filler / Reinforcement	Glass Fiber,25% Filler by Weight		
Additive	UV Stabilizer		
Features	High Impact Resistance		
	High Stiffness		
	Impact Copolymer		
Appearance	Black		
	Colors Available		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.09	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	8.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	57.9	MPa	ASTM D638
Flexural Modulus - 1% Secant	3690	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	130	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			ASTM D648
0.45 MPa, Unannealed	152	°C	
1.8 MPa, Unannealed	121	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

