

Huaxia Shenzhou PVDF DS206

Polyvinylidene Fluoride

Shandong Huaxia Shenzhou New Material Co., Ltd.

Message:

Huaxia Shenzhou PVDF DS206 is a Polyvinylidene Fluoride (PVDF) material. It is available in Asia Pacific, Europe, or North America.

General Information			
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.77 to 1.79	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/5.0 kg)	> 8.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	70 to 80		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	> 25.0	MPa	ASTM D638
Tensile Elongation (Break)	> 20	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature	165 to 175	°C	ASTM D3418
Additional Information	Nominal Value	Unit	Test Method
Thermal Decomposition Temperature ¹	> 410	°C	TGA
NOTE			

1. 1% Wt. Loss

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

