

Shanghai Potomer SG5

Rigid Polyvinyl Chloride

Shanghai Potomer International Trade Co., Ltd.

Message:

PVC suspension Resin is Calcium Carbide base, mainly used as sheet, pipe, window profiles and other molded parts.

APPLICATIONS: sewage pipes, pressure pipes, rigid profiles, window frames, electrical ducts

General Information		
Features	High Rigidity	
Uses	Electrical Parts	
	Piping	
	Profiles	
	Windows & Doors	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Apparent Density	> 0.45	g/cm ³
K (wear) Factor	66.0 to 68.0	
Sieve Analysis		
0.063mm sieve	> 90	%
0.25mm sieve	< 2.0	%
Viscosity	107 to 118	cm ³ /g
Volatile Matter	< 0.40	%
Fish Eye	< 20.0	pcs/400 cm ²
Impurities	< 16.0	pcs
Polymerization	1000 to 1100	
Whiteness - after 10min (160°C)	> 74	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT