# Shandong PA610 A6G7301

### Polyamide 610

Shandong Dongchen Engineering Plastics Co., Ltd.

#### Message:

 $Shandong\ PA610\ A6G7301\ is\ a\ Polyamide\ 610\ (Nylon\ 610)\ material\ filled\ with\ filler.\ It\ is\ available\ in\ Asia\ Pacific.$ 

Important attributes of Shandong PA610 A6G7301 are:

Good Dimensional Stability

**Good Processability** 

Heat Resistant

**High Stiffness** 

High Strength

General Information		
Filler / Reinforcement	Filler	
Features	Good Dimensional Stability	
	Good Processability	
	Good Wear Resistance	
	High Heat Resistance	
	High Stiffness	
	High Strength	
	Low to No Water Absorption	

Physical	Nominal Value	Unit
Ash Content	35	%
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	146	MPa
Tensile Strain (Break)	3.0	%
Flexural Modulus	7590	MPa
Flexural Stress	203	MPa
Impact	Nominal Value	Unit
Charpy Notched Impact Strength	17	kJ/m²
Charpy Unnotched Impact Strength	97	kJ/m²

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

