Kepamid® 1500SA

Polyamide 6

Korea Engineering Plastics Co., Ltd

Message:

Kepamid 1500SA is an impact modified polyamide-6. It exhibits good impact strength and mechanical properties. It is applicable to automotive, electrical, electronic, and industrial parts.

General Information				
Features	Good Impact Resistance			
Uses	Automotive Applications			
	Electrical Parts			
	Electrical/Electronic Applications			
	Industrial Applications			
Forms	Pellets			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.11	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (235°C/2.16				
kg)	15	g/10 min	ASTM D1238	
Molding Shrinkage - Flow (3.00 mm)	0.90 to 1.3	%	ASTM D955	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	115		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield, 23°C)	68.6	МРа	ASTM D638	
Tensile Elongation (Break, 23°C)	70	%	ASTM D638	
Flexural Modulus (23°C)	2350	MPa	ASTM D790	
Flexural Strength (23°C)	97.1	МРа	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (23°C)	150	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load			ASTM D648	
0.45 MPa, Unannealed	180	°C		
1.8 MPa, Unannealed	55.0	°C		
Melting Temperature	220	°C	DSC	
Flammability	Nominal Value		Test Method	
Flame Rating (0.800 mm)	НВ		UL 94	
Injection	Nominal Value	Unit		
Hopper Temperature	230 to 250	°C		
Rear Temperature	230 to 250	°C		
Middle Temperature	230 to 250	°C		

Front Temperature	230 to 250	°C	
Nozzle Temperature	230 to 250	°C	
Mold Temperature	40.0 to 100	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

