

MarFlex® 9608

High Density Polyethylene

Chevron Phillips Chemical Company LLC

Message:

MarFlex® 9608 is a High Density Polyethylene material. It is available in Latin America or North America for extrusion coating.

Important attributes of MarFlex® 9608 are:

Chemical Resistant

Good Processability

Good Stiffness

Scratch Resistant

Typical applications include:

Packaging

Additive/Masterbatch

Bags/Liners

General Information			
Features	Good Processability		
	Good Stiffness		
	Grease Resistant		
	Low Gel		
	Scratch Resistant		
Uses	Blending		
	Food Packaging		
	Liners		
	Packaging		
Forms	Pellets		
Processing Method	Extrusion Coating		
Physical	Nominal Value	Unit	Test Method
Density	0.962	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	8.0	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT