

# Biffa r-PP Black

Polypropylene

Biffa Polymers Ltd

## Message:

A versatile Polypropylene compound, r-PP black is particularly well suited for injection molding purposes. Melt strength can be modified to suit the users requirements to provide superior performance during molding. Impact strength of the material can also be tailored to ensure a more durable product.

General Information		
Appearance	Black	
Forms	Pellets	
Processing Method	Injection Molding	
Physical	Nominal Value	Unit
Density	0.900	g/cm <sup>3</sup>
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	7.0 to 9.0	g/10 min
Impact	Nominal Value	Unit
Notched Izod Impact Strength	11	kJ/m <sup>2</sup>
Additional Information	Nominal Value	Unit
Pellet Size	3.00 to 5.00	mm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

