

Moplen HP425J

Polypropylene Homopolymer

PolyMirae

Message:

Moplen HP425J is a Polypropylene Homopolymer (PP Homopolymer) material. It is available in Asia Pacific.

Important attributes of Moplen HP425J are:

- Food Contact Acceptable
- Good Aesthetics
- Good Processability
- Homopolymer
- Typical applications include:
 - Coating Applications
 - Film
 - Food Contact Applications

General Information			
Features	Barrier Resin		
	Food Contact Acceptable		
	General Purpose		
	Good Processability		
	Good Stretchability		
	Homopolymer		
	Opticals		
Uses	Bi-axially Oriented Film		
	General Purpose		
	Laminates		
Agency Ratings	FDA 21 CFR 177.1520		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	95		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield, Injection Molded)	34.3	MPa	ASTM D638
Tensile Elongation (Yield, Injection Molded)	12	%	ASTM D638
Flexural Modulus (Injection Molded)	1470	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, Injection Molded)	39	J/m	ASTM D256

Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed, Injection Molded)	102	°C	ASTM D648
Vicat Softening Temperature	152	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

