

Varcum 29738

Phenolic

Durez Corporation

Message:

Varcum 29738 is a two-step, powdered phenolic resin.
Molded brake block formulations.
Provides high heat resistance with excellent durability and wear resistance.
Fast cure and short flow characteristics permit fast press cycles and high rates of brake block production.

| General Information | | | |
|-----------------------------|-------------------------|------|-----------------|
| Features | Durable | | |
| | Fast Cure | | |
| | Fast Molding Cycle | | |
| | Good Wear Resistance | | |
| | High Heat Resistance | | |
| Uses | Automotive Applications | | |
| Forms | Powder | | |
| Additional Information | Nominal Value | Unit | Test Method |
| Hexa | 8.0 | % | Internal Method |
| Inclined Plate Flow (125°C) | 1.55 | cm | Internal Method |
| Screen Mesh ¹ | < 3.0 | % | Internal Method |
| NOTE | | | |
| 1. | 200 Mesh | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT