POLYPRO® SB9108

Polypropylene Copolymer

YUHWA Korea Petrochemical Ind. Co., Ltd.

Message:

POLYPRO® SB9108 is a Polypropylene Copolymer (PP Copolymer) material. It is available in Asia Pacific for injection molding. Important attributes of POLYPRO® SB9108 are:

Flame Rated

RoHS Compliant

Copolymer

High Gloss

High Stiffness

Typical applications include:

Automotive

Electrical/Electronic Applications

Food Contact Applications

General Information					
Features	Block Copolymer				
	Good Impact Resistance				
	High Gloss				
	High Stiffness				
Uses	Automotive Applications				
	Electrical/Electronic Applications				
Agency Ratings	FDA Food Contact, Unspecified Rating				
RoHS Compliance	RoHS Compliant				
Forms	Pellets				
Processing Method	Injection Molding	Injection Molding			
Physical	Nominal Value	Unit	Test Method		
Density	0.910	g/cm³	ASTM D1505		
Melt Mass-Flow Rate (MFR) (230°C/2 kg)	16 10	g/10 min	ASTM D1238		
Molding Shrinkage - Flow	1.4 to 1.8	%	Internal Method		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	97		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield)	29.4	MPa	ASTM D638		
Tensile Elongation (Break)	> 200	%	ASTM D638		
Flexural Modulus	1470	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact			ASTM D256		
-20°C	29	J/m			
25°C	98	J/m			

Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (1.8				
MPa, Unannealed)	130	°C	ASTM D648	
Vicat Softening Temperature	152	°C	ASTM D1525	
Peak Melting Temperature	168	°C	ASTM D3418	
Flammability	Nominal Value		Test Method	
Flame Rating (All Colors)	НВ		UL 94	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

