

# Europrene Lattice® 5584

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

## Message:

Europrene Lattice 5584 is an aqueous dispersion of a carboxylated styrene-butadiene copolymer obtained using synthetic anionic emulsifiers. It contains a non staining antioxidant

### Key Features

Europrene Lattice 5584 shows excellent performances at high filler loading

### Main Applications

Europrene Lattice 5584 is used for carpet backsizing and needlefelt impregnation when a medium-firm handle is required

General Information			
Additive	Antioxidant		
Features	Antioxidant		
	Copolymer		
Uses	Carpet Backing		
	Impregnation Applications		
Appearance	White		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Bound Styrene	60.0	%	ASTM D5775
pH	8.0		ASTM D1417
Solids Content	50.0	wt%	ASTM D1417
Brookfield Viscosity <sup>1</sup> (25°C)	400	mPa · s	ASTM D1417
NOTE			
1.	20 rpm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT