LightSpan® LS1-6941

Silicone

NuSil Technology

Message:

From LEDs to fiber optics, NuSil Technology's LightSpan™ brand product line delivers the most comprehensive line of refractive index matching adhesives, encapsulants and thermosets available.

The benefits of silicone include the following:

Thermal Stability

Low Ionic Species

Maintain Optical Clarity (90% minimum @ 400nm)

Low Moisture Absorption (<0.4%)

Optimization for UV Resistance

Adjustable Cure

Low Outgassing

Low Shrinkage, <1%

Low Modulus: Stress reduction for bonding materials with different coefficients of thermal expansion

Gernal Purpose: Optical Adhesives and Elastomers Comments: Tough, Tensile 750 psi, Tear 80 ppi

General Information			
Features	Good Thermal Stability		
	Good Toughness		
	Good UV Resistance		
	Low Moisture Absorption		
	Low Shrinkage		
	Low to No Outgassing		
Uses	Adhesives		
	Lenses		
Processing Method	Compression Molding		
	Injection Molding		
Optical	Nominal Value		
Refractive Index	1.410		
Thermoset	Nominal Value	Unit	
Thermoset Components			
Part A	Mix Ratio by Weight: 1.0		
Part B	Mix Ratio by Weight: 1.0		
Uncured Properties	Nominal Value	Unit	
Viscosity			
1	50	Pa·s	
2	75	Pa·s	
Curing Time (150°C)	0.50	hr	

Pot Life	> 1400	min
Cured Properties	Nominal Value	Unit
Shore Hardness (Shore A)	50	
Tensile Strength	5.17	MPa
Tensile Elongation at Break	310	%
NOTE		
1.	Part B	
2.	Part A	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

