

PADMEX 65080

High Density Polyethylene

Pemex Petroquímica

Message:

PADMEX 65080 is a High Density Polyethylene product. It is available in Europe, Latin America, or North America.

Characteristics include:

Antioxidant

Good UV Resistance

Lubricated

UV Stabilized

General Information			
Additive	Antioxidant		
	Lubricant		
	UV Stabilizer		
Features	Antioxidant		
	Good UV Resistance		
	Lubricated		
Physical	Nominal Value	Unit	Test Method
Density	0.965	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	8.0	g/10 min	ASTM D1238
Environmental Stress-Cracking Resistance	200	hr	ASTM D1693
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	72		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus - Secant	2320	MPa	ASTM D638
Tensile Strength (Yield)	29.4	MPa	ASTM D638
Tensile Elongation (Break)	> 500	%	ASTM D638
Flexural Modulus	1670	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	98	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	128	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

