

Braskem PE LL 5800 N

Linear Low Density Polyethylene

Braskem

Message:

LL5800N resin is a Linear Low Density Polyethylene, copolymer of octene-1, produced by solution process, for blown film extrusion with excellent mechanical properties. It contains processing aid and antioxidant additives.

General Information			
Additive	Antioxidant		
	Processing Aid		
Features	Antioxidant		
	Octene Comonomer		
Uses	Bags		
	Blending		
	Film		
	Liners		
	Packaging		
Agency Ratings	FDA 21 CFR 177.1520		
Processing Method	Blown Film		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.918	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	25	µm	ASTM D882
Tensile Strength			
MD : Break, 25 µm,Blown Film	50.0	MPa	
TD : Break, 25 µm,Blown Film	40.0	MPa	ASTM D882
Tensile Elongation			
MD : Break, 25 µm,Blown Film	920	%	
TD : Break, 25 µm,Blown Film	1200	%	
Flexural Modulus			ASTM D790
1% Secant, MD : 25 µm, Blown Film	150	MPa	
1% Secant, TD : 25 µm, Blown Film	170	MPa	
Dart Drop Impact (25 µm, Blown Film)	200	g	ASTM D1709
Elmendorf Tear Strength			ASTM D1922
MD : 25 µm, Blown Film	330	g	
TD : 25 µm, Blown Film	770	g	

Optical	Nominal Value	Unit	Test Method
Gloss (60°, 25.0 µm, Blown Film)	121		ASTM D2457
Haze (25.0 µm, Blown Film)	8.0	%	ASTM D1003

Extrusion	Nominal Value	Unit
Melt Temperature	200 to 220	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

