

Fixmaster 4 Minute Epoxy

Epoxy; Epoxide

Loctite®

Message:

Fixmaster 4 Minute Epoxy is an Epoxy; Epoxide (Epoxy) product. It is available in North America. Applications of Fixmaster 4 Minute Epoxy include adhesives/tapes and repairing material. Primary characteristic: high strength.

General Information			
Features	Fast Cure		
	High Strength		
Uses	Bonding		
	Repairing Material		
Forms	Pellets		
Hardness	Nominal Value	Test Method	
Durometer Hardness (Shore D)	70	ASTM D2240	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	27.6	MPa	ASTM D638
Compressive Strength	17.2	MPa	ASTM D695
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	71.1	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Pot Life (25°C)	2.0	min	
Demold Time (25°C)	4.0 to 6.0	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

