

Eco-Solutions GP8001T

Biodegradable Polymers
MINIMA Technoloy Co. Ltd.

Message:

Eco-Solutions GP8001T is a Biodegradable Polymers (Biodeg Polymers) material. It is available in Asia Pacific, Europe, or North America for extrusion coating or injection molding. Primary attribute of Eco-Solutions GP8001T: Eco-Friendly/Green.
Typical applications include:
Fabrics/Fibers
Film

General Information			
Features	Biodegradable		
	Compostable		
Uses	Film		
	Monofilaments		
Processing Method	Extrusion Coating		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.26	g/cm ³	JIS K7112
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	8.0	g/10 min	JIS K7210
Molding Shrinkage			Internal Method
Flow	1.3	%	
Across Flow	1.1	%	
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	105		JIS K7202
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			JIS K7113
Yield	35.0	MPa	
Break	25.0	MPa	
Tensile Elongation (Break)	100	%	JIS K7113
Flexural Modulus	550	MPa	JIS K7203
Flexural Strength	35.0	MPa	JIS K7203
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength	10	kJ/m ²	JIS K7110
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	91.0	°C	JIS K7207
Melting Temperature	110	°C	JIS K7121

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

