

Hanwha Total PP HTB52

Polypropylene

HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:

HTB52 is a high crystalline polypropylene that provides superior mechanical properties, including flexural modulus, surface hardness and tensile strength. Their use will also result in reduced product weight.

General Information			
Additive	Antistatic		
Features	Antistatic		
	Crystalline		
	Good Processability		
	Good Weather Resistance		
	High Heat Resistance		
	High Impact Resistance		
	High Stiffness		
	High Tensile Strength		
	Medium Hardness		
	Scratch Resistant		
Uses	Automotive Interior Parts		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.04	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	15	g/10 min	ASTM D1238
Molding Shrinkage - Flow	1.4	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	102		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	32.4	MPa	
Break	24.5	MPa	
Tensile Elongation (Break)	15	%	ASTM D638
Flexural Modulus	3140	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-30°C	29	J/m	
23°C	47	J/m	
Thermal	Nominal Value	Unit	Test Method

Deflection Temperature Under Load (0.45
MPa, Unannealed)

141

°C

ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

