

Fixmaster Roof and Gutter Sealant

Polyurethane

Loctite®

Message:

Fixmaster Roof and Gutter Sealant is a Polyurethane product. It is available in North America. Applications of Fixmaster Roof and Gutter Sealant include food contact applications and sealing applications.

Characteristics include:

Chemical Resistant

Good Flexibility

Good UV Resistance

Good Weather Resistance

General Information			
Features	Good Chemical Resistance		
	Good Flexibility		
	Good UV Resistance		
	Good Weather Resistance		
	Paintable		
Uses	Sealants		
Agency Ratings	USDA Unspecified Approval		
Forms	Pellets		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	3.45	MPa	ASTM D638
Tensile Elongation (Yield)	1000	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	82.2	°C	ASTM D794
Thermoset	Nominal Value	Unit	
Pot Life (25°C)	30	min	
Demold Time (25°C)	4300	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT