

Sinvicomp SGH2500

Flexible Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinvicomp SGH2500 is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific for extrusion.

Typical application of Sinvicomp SGH2500: Hose/Tubing

General Information			
Uses	Garden Hose		
Forms	Granules		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.32	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	98		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	17.2	MPa	ASTM D638
Tensile Elongation (Break)	210	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Thermal Stability ¹ (190°C)	30	min	BS 2782
NOTE			

1. Congo red@ 190 deg C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT