

# RTP 2099 X 138797

Unspecified  
RTP Company

Message:  
ESD Protection

General Information			
Features	Electrostatic discharge protection		
RoHS Compliance	Contact manufacturer		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.00	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (215°C/2.16 kg)	20	g/10 min	ASTM D1238
Moisture Content		%	
Injection	Nominal Value	Unit	
Drying Temperature	66	°C	
Drying Time	2.0 - 6.0	hr	
Processing (Melt) Temp	193 - 216	°C	
Injection instructions			

Do not exceed 520 °F (270 °C) melt temperature.Desiccant Type Dryer Required.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

