

KW Plastics KWR102CA25

High Density Polyethylene

KW Plastics

Message:

Copolymer High Density Polyethelene Post-Consumer Resin
Compounded with 25% Calcium Carbonate
CHARACTERISTICS
Increased stiffness, faster processing, improved heat deflection, lower cost.
Available as mixed color and pre-colored black.

General Information	
Filler / Reinforcement	Calcium Carbonate,25% Filler by Weight
Recycled Content	Yes
Features	Copolymer
	Good Stiffness
Appearance	Black
	Colors Available

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.17	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR)	0.43	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	24.1	MPa	ASTM D638
Tensile Elongation (Break)	11	%	ASTM D638
Flexural Modulus	1530	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	No Break		ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	45.8	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT