

Geon™ Vinyl Rigid Extrusion LR620 white 1046

Rigid Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™ Vinyl Rigid Extrusion LR620 white 1046 is a Rigid Polyvinyl Chloride product. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Construction Applications. Primary characteristic: eco-friendly/green.

General Information			
Recycled Content	Yes		
Features	General Purpose		
Uses	Building Materials		
	Profiles		
Forms	Cube		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.45	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 15 sec)	80		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus ¹	3010	MPa	ASTM D638
Tensile Strength ² (Yield)	40.7	MPa	ASTM D638
Flexural Modulus ³	2430	MPa	ASTM D790
Flexural Strength ⁴ (Yield)	66.4	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.18 mm, Compression Molded)	160	J/m	ASTM D256A
Drop Impact Resistance			ASTM D4226
-- ⁵	64.1	J/cm	
-- ⁶	79.2	J/cm	
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			ASTM D648
0.45 MPa, Unannealed	76.4	°C	
0.45 MPa, Annealed	78.5	°C	
1.8 MPa, Unannealed	72.7	°C	
1.8 MPa, Annealed	76.6	°C	
CLTE - Flow	6.3E-5	cm/cm/°C	ASTM D696
NOTE			
1.	Type I, 5.1 mm/min		
2.	Type I, 5.1 mm/min		
3.	13 mm/min		
4.	13 mm/min		

5.	Procedure A
6.	Procedure B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

