

Miraprene® QS1624D

Thermoplastic Polyolefin Elastomer

Mitsubishi Chemical Corporation

Message:

Miraprene® QS1624D is a Thermoplastic Polyolefin Elastomer (TPO (POE)) material. It is available in Asia Pacific for injection molding.

General Information			
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.05	g/cm ³	JIS K7112
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (10 sec)	80		JIS K6253
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	4.40	MPa	JIS K6251
Tensile Stress (Break)	13.2	MPa	JIS K6251
Tensile Elongation (Break)	700	%	JIS K6251

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

