

Vyncolit® EM7400-2

Epoxy; Epoxide

Vyncolit N.V.

Message:

EM 7400-2 is a polyaramide fiber reinforced epoxy molding compound, which features abrasion resistance and light weight.

General Information			
Filler / Reinforcement	Aramid fiber		
Features	Good wear resistance		
Appearance	Natural color		
Forms	flake		
Processing Method	Compression molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.08	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	85		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	6600	MPa	ASTM D790
Flexural Strength (Break)	76.0	MPa	ASTM D790
Additional Information			

Density - Specific Gravity, ASTM D792: 1 to 1.15 g/cm³

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

