Centrex® ST4800

Acrylonitrile Styrene Acrylate + TPE

Network Polymers, Inc.

Message:

Centrex® ST4800 is an Acrylonitrile Styrene Acrylate + TPE (ASA+TPE) product. It can be processed by coextrusion, injection molding, or thermoforming and is available in North America. Applications of Centrex® ST4800 include automotive, agricultural, marine applications and outdoor applications. Characteristics include: REACH Compliant ROHS Compliant WEEE Compliant Chemical Resistant Good UV Resistance

Features Durable Good Chemical Resistance Good UV Resistance Good Weather Resistance Low Gloss Soft Sound Damping Uses Automotive Instrument Panel Automotive Interior Parts Marine Applications Outdoor Applications Agency Ratings EC 1907/2006 (REACH) EU 2002/96/EC (WEEE) RoHS Compliance RoHS Compliant Processing Method Projectaion Molding Thermoforming Physical Nominal Value Unit Physical Nominal Value Mart Test Method Durometer Hardness (Shore A)	General Information			
Good UV Resistance God Wather Resistance Low Gloss Soft 	Features	Durable		
Good Weather Resistance Low Gloss Soft Sound DampingSelections Soft Sound DampingUsesAgricultural Applications Automotive Instrument Panel Automotive Instrument Panel Automotive Interior Parts Marine Applications Outdoor ApplicationsSelections Selections Display Control Parts Display Control Pa		Good Chemical Resistance		
Low Gloss Sofe Sound DampingUsesAgricultural Applications Automotive Instrument Panel Automotive Interior Parts Dudoor ApplicationsAgrecy RatingsEC 1907/2006 (REACH) EU 2002/96/EC (WEEE)RoHS ComplianceRHS CompliantFormsPelletsProcessing MethodCoextrusion Injection Molding ThermoformingPhysicalNominal ValueMutandase: How Rate (MFR) (230°C/34 kg)5PhysicalNominal ValueMarine Applications9/10 minMarine Applications35M D1238PhysicalNominal ValueMarine Applications15Marine Applications16Marine Applications161Marine Applicati		Good UV Resistance		
Soft Sound DampingUsesAgicultural Applications Automotive Instrument Panel Automotive Interior Parts Marine Applications Datione ApplicationsAgency RatingsEC 1907/2006 (REACH) EU 2002/96/EC (WEEE)RoHS ComplianceROHS CompliantFormsPelletsProcessing MethodCextrusion Injection Molding ThermoformingPhysicalNoinal ValueMarine ApplicationsSti D1230PhysicalNoinal ValueMarine ApplicationsSti D1230PhysicalNoinal ValueMarine ApplicationsSti D1230PhysicalNoinal ValueMarine ApplicationsSti D1230Marine ApplicationsMite ApplicationsPhysicalNoinal ValueMarine ApplicationsMite ApplicationsPhysicalNoinal ValueMarine ApplicationsSti D1230Marine ApplicationsMite ApplicationsPhysicalNoinal ValueMarine ApplicationsApplicationsMarine ApplicationsMite ApplicationsPhysicalNoinal ValueMarine ApplicationsApplicationsMarine ApplicationsMite ApplicationsMarine Applications <t< td=""><td></td><td>Good Weather Resistance</td><td></td><td></td></t<>		Good Weather Resistance		
Sound Damping Uses Agricultural Applications Automotive Instrument Panel Automotive Interior Parts Marine Applications Marine Applications Marine Applications Construitions Version Rency Ratings EC 1907/2006 (REACH) EU 2002/96/EC (WEEE) Forms Pellets Processing Method Coextrusion Injection Molding Thermoforming Physical Nominal Value Methods-Flow Rate (MFR) (230°C/3.8 kg) 15 Marinal Value Unit Marinal Value Ontil 230 Hardness Nominal Value Jurmeter Hardness (Shore A) 46		Low Gloss		
UsesAgricultural Applications Automotive Instrument Panel Automotive Interior Parts Marine Applications Outdoor Applications Outdoor ApplicationsLet applications Control ApplicationsAgency RatingsEC 1907/2006 (REACH) EU 2002/96/EC (WEEE)Let applicationsRoHS ComplianceRoHS CompliantLet applicationsFormsPelletsLet applicationsProcessing MethodCoextrusion Injection Molding ThermoformingUnitTest MethodPhysicalNominal ValueUnitTest MethodMethods-Flow Rate (MFR) (230°C/38 kg)15g/10 minASTM D1238HardnessNominal ValueUnitTest MethodDrometer Hardness (Shore A)46Let applicationsASTM D2240		Soft		
Automotive Instrument Panel Automotive Interior Parts Marine Applications Outdoor ApplicationsSelectionsAgency RatingsEC 1907/2006 (REACH) EU 2002/96/EC (WEEE)SelectionsRoHS ComplianceRoHS CompliantSelectionsFormsPelletsSelectionsProcessing MethodCoextrusion Injection Molding ThermoformingSelectionsPhysicalNominal ValueUnitTest MethodMeth Mass-Flow Rate (MFR) (230°C/3.8 kg)150/10 minASTM D1238PhysicalNominal ValueUnitTest MethodMethodsSoft Marcel46SelectionsASTM D1234		Sound Damping		
Automotive Instrument Panel Automotive Interior Parts Marine Applications Outdoor ApplicationsSelectionsAgency RatingsEC 1907/2006 (REACH) EU 2002/96/EC (WEEE)SelectionsRoHS ComplianceRoHS CompliantSelectionsFormsPelletsSelectionsProcessing MethodCoextrusion Injection Molding ThermoformingSelectionsPhysicalNominal ValueUnitTest MethodMeth Mass-Flow Rate (MFR) (230°C/3.8 kg)150/10 minASTM D1238PhysicalNominal ValueUnitTest MethodMethodsSoft Marcel46SelectionsASTM D1234	Uses	Agricultural Applications		
Marine Applications Outdoor ApplicationsAgency RatingsEC 1907/2006 (REACH) EU 2002/96/EC (WEEE)ROHS ComplianceROHS CompliantFormsPelletsProcessing MethodCoextrusion Injection Molding ThermoformingPhysicalNominal ValueMominal ValueUnitMet Mass-Flow Rate (MFR) (230°C/38 kg)5Marinal ValueUnitMet Mass-Flow Rate (MFR) (230°C/38 kg)15Mominal ValueUnitMarinal ValueUnitMarinal ValueMarinal ValueMurinal ValueMarinal Va				
Qutdor ApplicationsAgency RatingsEC 1907/2006 (REACH) EU 2002/96/EC (WEEE)RoHS ComplianceRoHS CompliantFormsPelletsProcessing MethodCoextrusion Injection Molding ThermoformingPhysicalNominal ValueMet Mass-Flow Rate (MFR) (230°C/38 kg)IMet Mass-Flow Rate (MFR) (230°C/38 kg)IMandalageUnitMathdessNominal ValueMunderseUnitMathdess (Shore A)4MathdessASTM D2240		Automotive Interior Parts		
Agency RatingsEC 1907/2006 (REACH) EU 2002/96/EC (WEEE)EC 1907/2006 (REACH) EU 2002/96/EC (WEEE)RoHS ComplianceRoHS Compliant		Marine Applications		
EU 2002/96/EC (WEEE) RoHS Compliance RoHS Compliant Forms Pellets Processing Method Coextrusion Injection Molding Thermoforming Injection Molding Physical Nominal Value Unit Meth Mass-Flow Rate (MFR) (230°C/3.8 kg) 15 g/10 min ASTM D1238 Hardness Nominal Value Unit Test Method Durometer Hardness (Shore A) 45 Unit Test Method		Outdoor Applications		
RoHS Compliance RoHS Compliant Forms Pellets Processing Method Coextrusion Injection Molding Thermoforming Thermoforming Physical Nominal Value Unit Meth Mass-Flow Rate (MFR) (230°C/3.8 kg) 15 g/10 min ASTM D1238 Hardness Nominal Value Unit Test Method	Agency Ratings	EC 1907/2006 (REACH)		
FormsPelletsProcessing MethodCoextrusionInjection Molding ThermoformingInjection Molding ThermoformingPhysicalNominal ValueUnitMelt Mass-Flow Rate (MFR) (230°C/3.8 kg)Ig/10 minHardnessNominal ValueUnitDurometer Hardness (Shore A)4X		EU 2002/96/EC (WEEE)		
Processing MethodCoextrusion Injection Molding ThermoformingSubscienceSubscienceSubsciencePhysicalNominal ValueUnitTest MethodMelt Mass-Flow Rate (MFR) (230°C/3.8 kg)15g/10 minASTM D1238HardnessNominal ValueUnitTest MethodDurometer Hardness (Shore A)45Store A)ASTM D2240	RoHS Compliance	RoHS Compliant		
Injection Molding ThermoformingPhysicalNominal ValueUnitTest MethodMelt Mass-Flow Rate (MFR) (230°C).38 kg)15g/10 minASTM D1238HardnessNominal ValueUnitTest MethodDurometer Hardness (Shore A)46STM D12240	Forms	Pellets		
Thermoforming Physical Nominal Value Unit Test Method Melt Mass-Flow Rate (MFR) (230°C/3.8 kg) 15 g/10 min ASTM D1238 Hardness Nominal Value Unit Test Method Durometer Hardness (Shore A) 46 ASTM D2240	Processing Method	Coextrusion		
Physical Nominal Value Unit Test Method Melt Mass-Flow Rate (MFR) (230°C/3.8 kg) 15 g/10 min ASTM D1238 Hardness Nominal Value Unit Test Method Durometer Hardness (Shore A) 46 ASTM D2240		Injection Molding		
Melt Mass-Flow Rate (MFR) (230°C/3.8 kg) 15 g/10 min ASTM D1238 Hardness Nominal Value Unit Test Method Durometer Hardness (Shore A) 46 ASTM D2240		Thermoforming		
Melt Mass-Flow Rate (MFR) (230°C/3.8 kg) 15 g/10 min ASTM D1238 Hardness Nominal Value Unit Test Method Durometer Hardness (Shore A) 46 ASTM D2240	Physical	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A) 46 ASTM D2240	Melt Mass-Flow Rate (MFR) (230°C/3.8 kg)	15	g/10 min	ASTM D1238
	Hardness	Nominal Value	Unit	Test Method
Impact Nominal Value Unit Test Method	Durometer Hardness (Shore A)	46		ASTM D2240
	Impact	Nominal Value	Unit	Test Method

		ASTM D3763
6.00	J	
8.00	J	
Nominal Value	Unit	Test Method
42	mm/min	ISO 3795
Nominal Value		Test Method
10		ASTM D523
Nominal Value	Unit	
65.6	°C	
4.0 to 6.0	hr	
0.10	%	
15	%	
	8.00 Nominal Value 42 Nominal Value 10 Nominal Value 65.6 4.0 to 6.0 0.10	8.00 J Nominal Value Unit 42 mm/min Nominal Value J 10 Unit 65.6 °C 4.0 to 6.0 hr 0.10 %

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

