

# Braskem PE HF0131XP

Linear Low Density Polyethylene

Braskem

## Message:

The HF0131XP is a linear low density polyethylene that shows an excellent processability and mate finish.

Additive:

Antioxidants

Lubricant

Applications:

Hamburger bags.

Process:

Blown Film Extrusion.

General Information			
Additive	Antioxidation		
	Lubricant		
Features	Antioxidation		
	Workability, good		
	Lubrication		
Uses	Blown Film		
	Films		
	Bags		
Agency Ratings	FDA 21 CFR 177.1520		
Processing Method	Blow film		
Physical	Nominal Value	Unit	Test Method
Density	0.937	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/21.6 kg)	11	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Elmendorf Tear Strength			ASTM D1922
MD: 20 µm, blown film	5.0	g	ASTM D1922
TD: 20 µm, blown film	960	g	ASTM D1922

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

