Santoprene™ 101-55W255

Thermoplastic Vulcanizate

ExxonMobil Chemical

Message:

It is a soft, black thermoplastic vulcanized elastomer (TPV) in the thermoplastic elastomer (TPE) series. This material is designed for use in household washing machines and dishwashers and contains a stable system to prevent catalytic degradation of copper and other metals. This brand of Sanduping TPV is a shear rate dependent product that can be processed on conventional thermoplastic injection molding or extrusion molding equipment. This is a polyolefin-based material that can be recycled in the production process.

General Information					
UL YellowCard	E80017-564849				
Features	Low compressive deformability				
	Recyclable materials				
	Ozone resistance				
	Copper contact stability				
Uses	Washer				
	Home appliance components				
	Seals				
Agency Ratings	UL QMFZ2				
	UL QMFZ8				
RoHS Compliance	RoHS compliance				
UL File Number	E80017				
Appearance	Black				
Forms	Particle				
Processing Method	Multiple injection molding				
	Co-extrusion molding				
	Extrusion				
	Sheet extrusion molding				
	Profile extrusion molding				
	Injection molding				
Physical	Nominal Value	Unit	Test Method		

Nominal Value	Unit	Test Method
0.968	g/cm³	ASTM D792
0.970	g/cm³	ISO 1183
Nominal Value	Unit	Test Method
ds,		
61		ISO 868
	0.968 0.970 Nominal Value	0.968 g/cm³ 0.970 g/cm³ Nominal Value Unit

Elastomers	Nominal Value	Unit	Test Method				
Tensile Stress - Across Flow (100% Strain,							
23°C)	1.80	MPa	ASTM D412, ISO 37				
Tensile Strength - Across Flow (Break,							
23°C)	5.20	MPa	ASTM D412, ISO 37				
Tensile Elongation - Across Flow (Break,							
23°C)	510	%	ASTM D412, ISO 37				
Flammability	Nominal Value		Test Method				
Flame Rating			UL 94				
1.50 mm	НВ		UL 94				
3.00 mm	НВ		UL 94				

Additional Information

如果适用,这是基于扇形浇口注塑成型的平板测试结果.拉伸强度,伸长率和拉伸应力沿垂直流动方向测定 - ISO 1 型,ASTM die C.从埃克森美孚欧洲分支机构直接购买的所有产品都符合 REACH 法规. 对于埃克森 美孚未进口至欧洲的产品,用户应自行评估其是否满足 REACH 法规.

Legal statement

未经埃克森美孚化工书面允许,这种产品包括其产品名称,不得在任何医疗应用领域予以使用或有关详细的产品监管信息,请联系客户服务.

Injection instructions

Santoprene TPV与乙缩醛和PVC不相容.更多关于加工和模具设计的信息,请查阅我们的《注射成型指南》.

Extrusion instructions

Santoprene TPV与乙缩醛和PVC不相容.更多关于加工和模具设计的信息,请查阅我们的《挤出成型指南》.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

