

SIBUR PE 15803-020

Low Density Polyethylene

SIBUR, LLC

Message:

PE 15803-020 is a film grade of low-density polyethylene. The grade is additive free.

Typical Applications:

PE 15803-020 is recommended for film extrusion, including thin films, food packaging and technical films. It complies with EU Food Contact Regulations.

General Information		
Features	Additive Free	
Uses	Film	
	Food Packaging	
Agency Ratings	EC 1907/2006 (REACH)	
	EU Food Contact, Unspecified Rating	
Forms	Pellets	
Physical	Nominal Value	Unit
Density	0.919	g/cm ³
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min
Appearance - Process test for film	B	%
Extractables		
Mass fraction	0.4	%
Odour and taste of aqueous extract	1.0	points
Mechanical	Nominal Value	Unit
Tensile Stress ¹		
Yield	9.50	MPa
Break	11.7	MPa
Tensile Strain ² (Break)	600	%
NOTE		
1.	500 mm/min	
2.	500 mm/min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

