

# ALKAMIX™ MB6007

Linear Low Density Polyethylene

Qenos Pty Ltd

## Message:

ALKAMIX MB6007 is a slip masterbatch formulated with Oleamide at a concentration of 1.1 percent.

ALKAMIX MB6007 can be added to polyethylene during extrusion to reduce the coefficient of friction. The level required will vary according to coefficient of friction desired; gauge of film and other factors such as the presence of other additives (including antiblocks, colourants / pigments, etc...).

The maximum level of addition of MB6007 based on both good manufacturing practice and to ensure conformance to the requirements to the United States Food and Drug Administration Regulations CFR21 is 15 percent, when added to a polyethylene formulation free of any slip additives.

General Information			
Additive	Slip (1%)		
Features	Slip		
Uses	Blending		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm <sup>3</sup>	ASTM D1505

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT