

NYLOY® N-0020N-V0

Polyamide 6

Nytex Composites Co., Ltd.

Message:

NYLOY®N-0020N-V0 is a polyamide 6 (nylon 6) material. This product is available in North America or Asia Pacific.

NYLOY®The main features of the N-0020N-V0 are:

flame retardant/rated flame

Flame Retardant

General Information			
UL YellowCard	E135714-222629		
Additive	Flame retardancy		
Features	Flame retardancy		
Appearance	Natural color		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.00	g/cm ³	ASTM D792
Molding Shrinkage - Flow	0.70 - 1.4	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	73.6	MPa	ASTM D638
Tensile Elongation (Break)	10	%	ASTM D638
Flexural Modulus	2940	MPa	ASTM D790
Flexural Strength	108	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.18 mm)	40	J/m	ASTM D256
Flammability	Nominal Value	Test Method	
Flame Rating (1.6 mm)	V-2	UL 94	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT