

Paracril® 32.55XL

Acrylonitrile Butadiene Rubber

INSA

Message:

Description:

Partially crosslinked.

Excellent green strength.

Smooth extrusion.

Lower die swell.

Non staining and non discoloring stabilizer.

Applications:

Pvc modification.

Extrusions and lathe cut gaskets.

Calendered goods.

General Information			
Features	Crosslinkable		
	Good Green Strength		
	Good Processability		
	Low Die Swell		
	Stain Resistant		
Uses	Gaskets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.990	g/cm ³	ASTM D297
Mooney Viscosity (ML 1+4, 100°C)	48 to 62	MU	ASTM D1646
ACN Content - Bound	31.0 to 34.0	wt%	Internal Method
Ash Content	< 0.8	wt%	ASTM D5667
Volatile Matter	< 1.0	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT