

Borealis PP TD215BF

Polypropylene Terpolymer

Borealis AG

Message:

TD215BF is a C2/C4 terpolymer

This grade is designed for sealing layers of oriented and non oriented films

CAS-No. 25895-47-0

| General Information | | | |
|---|-------------------------------------|----------|-----------------|
| Additive | Antiblock | | |
| Features | Med.-Wide Molecular Weight Distrib. | | |
| | Recyclable Material | | |
| Uses | Film | | |
| | Food Packaging | | |
| Processing Method | Coextrusion | | |
| Physical | Nominal Value | Unit | Test Method |
| Melt Mass-Flow Rate (MFR) (230°C/2.16 kg) | 6.0 | g/10 min | ISO 1133 |
| Thermal | Nominal Value | Unit | Test Method |
| Melting Temperature | 130 | °C | ISO 11357-3 |
| Additional Information | Nominal Value | Unit | Test Method |
| Sealing Initial Temperature - 3 N | 103 | °C | Internal Method |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT