Boltaron 6800

Acrylic (PMMA) + PVC

Boltaron Performance Products

Message:

Boltaron 6800 is a proprietary, fire retardant, press laminated ABS/PVC alloy sheet designed to meet stringent FAA flammability requirements and UL Standard 94 V-0. Boltaron 6800 offers excellent impact strength, abrasion resistance, stain and chemical resistance, and superior thermoformability.

Flame Retardant

Colors: Custom Gauges: .031 to .250

Sheet Sizes: 50" x99" & 55.5" x122" (untrimmed)

Textures: Haircell

Industrial Smooth

General Information

Crush Falmuth Suede Morocco

Features

	Good Abrasion Resistance		
	Good Chemical Resistance		
	Good UV Resistance		
	High Impact Resistance		
	Stain Resistant		
Uses	Aircraft Interiors		
	Laminates		
Agency Ratings	FAR 25.853		
Appearance	Colors Available		
Forms	Sheet		
Processing Method	Press Molding		
	Thermoforming		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.30	g/cm³	ASTM D792
Molding Shrinkage - Flow	0.50 to 0.70	%	
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	105		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	41.4	MPa	ASTM D638
Flexural Modulus	2340	MPa	ASTM D790
Flexural Strength (Yield)	62.1	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method

Notched Izod Impact	270 to 530	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8			
MPa, Annealed)	72.2	°C	ASTM D648
Flammability	Nominal Value	Unit	Test Method
	12.0		
1			
FAA Flammability ¹	60.0	sec	FAR 25.853
Radiant Panel Flame Spread Index (3.18			
mm)	< 17.0		ASTM E162
Forming Temperature	168 to 185	°C	
NOTE			
1.	Pass		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

