

# TAISOX 8050

High Density Polyethylene  
Formosa Plastics Corporation

Message:

TAISOX 8050 is a high density polyethylene material. This product is available in North America, Europe or Asia Pacific region. The processing method is injection molding.

The main features of TAISOX 8050 are:

Good processability

Hard

Impact resistance

Typical application areas include:

container

Seat

General Information			
Features	Rigidity, high		
	High density		
	Impact resistance, good		
	Workability, good		
Uses	Loading box		
	Seat		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	0.960	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	6.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	70		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	30.4	MPa	ASTM D638
Fracture	23.5	MPa	ASTM D638
Tensile Elongation (Break)	1000	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Tensile Impact Strength	137	kJ/m <sup>2</sup>	ASTM D1822
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-70.0	°C	ASTM D746
Vicat Softening Temperature	127	°C	ASTM D1525
Melting Temperature	135	°C	
Additional Information			

Notched Izod Impact Strength, ASTM D256: 6 kg-cm/cm<sup>2</sup>

Injection	Nominal Value	Unit
Processing (Melt) Temp	170 - 190	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

