

TEKALOY™ T80

Acrylonitrile Butadiene Styrene + PBT

Mando Advanced Materials Co., Ltd.

Message:

TEKALOY™ T80 is an Acrylonitrile Butadiene Styrene + PBT (ABS+PBT) product. It is available in Asia Pacific.

Characteristics include:

Flame Rated

Good Dimensional Stability

General Information			
Features	Good Dimensional Stability		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.08	g/cm ³	ASTM D792
Molding Shrinkage ¹			ASTM D955
Flow	0.70	%	
Across Flow	0.70	%	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	47.1	MPa	ASTM D638
Tensile Elongation (Break)	30	%	ASTM D638
Flexural Modulus	3140	MPa	ASTM D790
Flexural Strength	88.3	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	180	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			ASTM D648
0.45 MPa, Unannealed	86.0	°C	
1.8 MPa, Unannealed	85.0	°C	
Flammability	Nominal Value		Test Method
Flame Rating	HB		UL 94
Injection	Nominal Value	Unit	
Processing (Melt) Temp	210 to 250	°C	
Mold Temperature	60.0 to 80.0	°C	
NOTE			
1.	60°C Mold Temperature		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

