

Galoo GP-PP-128

Polypropylene

Galoo Plastics

Message:

Black colored polypropylene compound

General Information			
Recycled Content	Yes		
Appearance	Black		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.880 to 0.920	g/cm ³	Internal Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	10 to 14	g/10 min	ISO 1133
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D)	> 62		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			ISO 527-2
Yield	> 20.0	MPa	
Break	> 11.0	MPa	
Tensile Strain (Break)	> 30	%	ISO 527-2
Flexural Modulus	950	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	> 7.0	kJ/m ²	ISO 180
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	> 48.0	°C	ISO 75-2/A
Vicat Softening Temperature	> 120	°C	ISO 306/A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT