Xuchuan 1007N/B-5301

Thermoplastic Polyurethane Elastomer (Polyether)

Xuchuan Chemical (Suzhou) Co., Ltd

Message:

Xuchuan 1007N/B-5301 is a Thermoplastic Polyurethane Elastomer (Polyether) (TPU-Polyether) product. It is available in Asia Pacific. Typical application: Consumer Goods. Primary characteristic: good weather resistance.

General Information			
Features	Good Weather Resistance		
	Hydrolysis Resistant		
Uses	Footwear		
0363	Tires		
	THES		
Physical	Nominal Value	Unit	
Density	0.400 to 0.650	g/cm³	
Density			
A-1007N : 40°C	1.010 to 1.020	g/cm³	
B-5301 : 40°C	1.080 to 1.200	g/cm³	
Viscosity			
A-1007N : 40°C	400 to 800	mPa·s	
B-5301 : 40°C	300 to 600	mPa·s	
Akron Abrasion	0.0500 to 0.100	cm³/1.61 km	
Cream Time	8.0 to 10.0	sec	
End of Rise Time	1.0 to 1.2	min	
Free Rise Foam Density	200 to 320	kg/m³	
Hydrolysis Strength Retention (70°C) ¹	> 90	%	
Preheat Temperature			
Part A	50 to 60	°C	
Part B	60 to 70	°C	
Preheat Time			
Part A	2.0 to 4.0	hr	
Part B	10.0 to 15.0	hr	
Processing Temperature			
Part A	30 to 35	°C	
Part B	35 to 40	°C	
Resilience	30 to 40	%	
Hardness	Nominal Value	Unit	
Durometer Hardness (Shore A)	50 to 80		
Elastomers	Nominal Value	Unit	

Tensile Strength (Break)	3.00 to 5.00	MPa	
Tensile Elongation (Break)	290 to 360	%	
Tear Strength	10.0 to 20.0	kN/m	
Thermoset	Nominal Value	Unit	
Thermoset Components			
Part A	Mix Ratio by Weight: 100		
Part B	Mix Ratio by Weight: 91 to	Mix Ratio by Weight: 91 to 93	
Demold Time	5.0 to 7.0	min	
Injection	Nominal Value	Unit	
Mold Temperature	35.0 to 45.0	°C	
NOTE			
1.	168 hr, 95% RH		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

