Reon 60-11

Polyvinyl Chloride Homopolymer

Reliance Industries Limited

Message:

60-11 is a low molecular weight suspension type PVC resin suitable for blow moulding and calendering applications. It is specially recommended for BM / SBM of bottles and calendering of sheets. Its combination of low molecular weight with high melt flow makes it suitable for easy processing of calendered, blow moulded and injection moulded items. It has a low fish eye and low dark resin count which makes it suitable for transparent applications. Uniform coarseness of the grains of this resin results in easy bulk handling, optimum requirement of lubricant and more uniform fluxing in the barrel.

General Information					
Features	Good Processability				
	Homopolymer				
	Low Molecular Weight				
Uses	Bottles				
	Containers				
	Cosmetic Packaging				
	Cosmetics				
	Film				
	Packaging				
	Sheet				
Agency Ratings	IS 10151				
Appearance	Clear/Transparent				
Processing Method	Blow Molding				
	Calendering				
	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Apparent Density	0.49 to 0.55	g/cm³	ASTM D1895		
K-Value ¹	60.0				
Inherent Viscosity	0.75		ASTM D1243		
Particle Size - Retention on ASTM 30 mesh	< 0.00500	%			
Particle Size Distribution			ASTM D1921		
Retention on ASTM 40 mesh	< 0.10	%			
Retention on ASTM 60 mesh	< 2.0	%			
Through ASTM 140 mesh	< 40	%			
Heat Loss	< 0.30	%	ASTM D3030		
Dark Resin - for 100 g resin	< 4.00	count/g			
Fish Eye - Blown Film Method	< 10.0				

Flow Time	< 25.0	sec	ASTM D1895
Porosity - DOP	0.220 to 0.340	cm³/g	ASTM D3367
Residual Vinyl Chloride Monomer	< 2	ppm	ASTM D3749
NOTE			
1.	@ 1% in cyclohexanone		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

