

Sevrene® 4250-67A

Polyvinyl Chloride

Vi-Chem Corporation

Message:

Sevrene® 4250-67A is a Polyvinyl Chloride material. It is available in North America.

General Information			
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.18	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) ¹ (230°C/2.16 kg)	38	g/10 min	ISO 1133
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	72		ASTM D2240, ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress ² (Yield)	3.90	MPa	ISO 527-2
Tensile Strain (Break)	460	%	ISO 527-2/5A
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	3.90	MPa	ASTM D412A
Tensile Elongation (Break)	460	%	ASTM D412
Tear Strength ³	22.0	kN/m	ASTM D624
NOTE			
1.	Procedure B		
2.	Type 5A		
3.	Die C		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT